



3-Phase LED track spotlight with Nordic track adapter available in white, grey and black. Available in CCT from 2700K till 5700K in CRI80 or CRI90, also in special colors for retail use. Reflectors with 20°, 36° or 50° and various accessories allow installations in a large range of applications. Protective glass and honeycomb on request available.



Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>2.022B0A830003600000</u>	1600Lm	14W	3000K	(RA) >80	White (RAL 9003)	20°/36°/50°
<u>2.022B0A840003600000</u>	1700Lm	14W	4000K	(RA) >80	White (RAL 9003)	20°/36°/50°
<u>2.022B0A930003600000</u>	1350Lm	14W	3000K	(RA) >90	White (RAL 9003)	20°/36°/50°
<u>2.022B0A940PW3600000</u>	1450Lm	14W	4000K	(RA) >90	White (RAL 9003)	20°/36°/50°
<u>2.022C0A830003600000</u>	2250Lm	18.5W	3000K	(RA) >80	White (RAL 9003)	20°/36°/50°
<u>2.022C0A930003600000</u>	1800Lm	18.5W	3000K	(RA) >90	White (RAL 9003)	20°/36°/50°
<u>2.022C0A940PW3600000</u>	2000Lm	18.5W	4000K	(RA) >90	White (RAL 9003)	20°/36°/50°
<u>2.022D0A840003600000</u>	2350Lm	18.5W	4000K	(RA) >80	White (RAL 9003)	20°/36°/50°
<u>2.022E0A830003600000</u>	3000Lm	27W	3000K	(RA) >80	White (RAL 9003)	20°/36°/50°
<u>2.022E0A840003600000</u>	3150Lm	27W	4000K	(RA) >80	White (RAL 9003)	20°/36°/50°
<u>2.022E0A930003600000</u>	2800Lm	30W	3000K	(RA) >90	White (RAL 9003)	20°/36°/50°
<u>2.022E0A940PW3600000</u>	3000Lm	30W	4000K	(RA) >90	White (RAL 9003)	20°/36°/50°
<u>2.022B0C830003600000</u>	1600Lm	14W	3000K	(RA) >80	Grey (RAL 9006)	20°/36°/50°
<u>2.022B0C840003600000</u>	1700Lm	14W	4000K	(RA) >80	Grey (RAL 9006)	20°/36°/50°
<u>2.022B0C930003600000</u>	1350Lm	14W	3000K	(RA) >90	Grey (RAL 9006)	20°/36°/50°
<u>2.022B0C940PW3600000</u>	1450Lm	14W	4000K	(RA) >90	Grey (RAL 9006)	20°/36°/50°
<u>2.022C0C830003600000</u>	2250Lm	18.5W	3000K	(RA) >80	Grey (RAL 9006)	20°/36°/50°
<u>2.022C0C930003600000</u>	1800Lm	18.5W	3000K	(RA) >90	Grey (RAL 9006)	20°/36°/50°

Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>2.022C0C940PW3600000</u>	2000Lm	18.5W	4000K	(RA) >90	Grey (RAL 9006)	20°/36°/50°
<u>2.022D0C840003600000</u>	2350Lm	18.5W	4000K	(RA) >80	Grey (RAL 9006)	20°/36°/50°
<u>2.022E0C830003600000</u>	3000Lm	27W	3000K	(RA) >80	Grey (RAL 9006)	20°/36°/50°
<u>2.022E0C840003600000</u>	3150Lm	27W	4000K	(RA) >80	Grey (RAL 9006)	20°/36°/50°
<u>2.022E0C930003600000</u>	2800Lm	30W	3000K	(RA) >90	Grey (RAL 9006)	20°/36°/50°
<u>2.022E0C940PW3600000</u>	3000Lm	30W	4000K	(RA) >90	Grey (RAL 9006)	20°/36°/50°
<u>2.022B0B830003600000</u>	1600Lm	14W	3000K	(RA) >80	Black (RAL 9005)	20°/36°/50°
<u>2.022B0B840003600000</u>	1700Lm	14W	4000K	(RA) >80	Black (RAL 9005)	20°/36°/50°
<u>2.022B0B930003600000</u>	1350Lm	14W	3000K	(RA) >90	Black (RAL 9005)	20°/36°/50°
<u>2.022B0B940PW3600000</u>	1450Lm	14W	4000K	(RA) >90	Black (RAL 9005)	20°/36°/50°
<u>2.022C0B830003600000</u>	2250Lm	18.5W	3000K	(RA) >80	Black (RAL 9005)	20°/36°/50°
<u>2.022C0B930003600000</u>	1800Lm	18.5W	3000K	(RA) >90	Black (RAL 9005)	20°/36°/50°
<u>2.022C0B940PW3600000</u>	2000Lm	18.5W	4000K	(RA) >90	Black (RAL 9005)	20°/36°/50°
<u>2.022D0B840003600000</u>	2350Lm	18.5W	4000K	(RA) >80	Black (RAL 9005)	20°/36°/50°
<u>2.022E0B830003600000</u>	3000Lm	27W	3000K	(RA) >80	Black (RAL 9005)	20°/36°/50°
<u>2.022E0B840003600000</u>	3150Lm	27W	4000K	(RA) >80	Black (RAL 9005)	20°/36°/50°
<u>2.022E0B930003600000</u>	2800Lm	30W	3000K	(RA) >90	Black (RAL 9005)	20°/36°/50°
<u>2.022E0B940PW3600000</u>	3000Lm	30W	4000K	(RA) >90	Black (RAL 9005)	20°/36°/50°

