



Recessed LED downlight supplied available in white, grey and black. Available in CCT from 2700K till 5700K in CRI80 or CRI90 and also in special colors for retail use. IP65. The luminaire is equipped with a clear protection glass.

PREMIUM WHITE	CRISP WHITE				CASAMBI	



Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.004A0A830003000000</u>	1250Lm	9.5W	3000K	(RA) >80	White (RAL 9003)	15°/30°/45°/60°
<u>1.004A0A930003000000</u>	1050Lm	9.5W	3000K	(RA) >90	White (RAL 9003)	15°/30°/45°/60°
<u>1.004A0A940PW3000000</u>	1100Lm	9.5W	4000K	(RA) >90	White (RAL 9003)	15°/30°/45°/60°
<u>1.004B0A840003000000</u>	1300Lm	9.5W	4000K	(RA) >80	White (RAL 9003)	15°/30°/45°/60°
<u>1.004C0A930003000000</u>	2000Lm	18.5W	3000K	(RA) >90	White (RAL 9003)	15°/30°/45°/60°
<u>1.004C0A940PW3000000</u>	2150Lm	18.5W	4000K	(RA) >90	White (RAL 9003)	15°/30°/45°/60°
<u>1.004D0A830003000000</u>	2400Lm	18.5W	3000K	(RA) >80	White (RAL 9003)	15°/30°/45°/60°
<u>1.004D0A840003000000</u>	2500Lm	18.5W	4000K	(RA) >80	White (RAL 9003)	15°/30°/45°/60°
<u>1.004E0A830003000000</u>	3250Lm	26W	3000K	(RA) >80	White (RAL 9003)	15°/30°/45°/60°
<u>1.004E0A930003000000</u>	3000Lm	30W	3000K	(RA) >90	White (RAL 9003)	15°/30°/45°/60°
<u>1.004E0A940PW3000000</u>	3200Lm	30W	4000K	(RA) >90	White (RAL 9003)	15°/30°/45°/60°
<u>1.004F0A840003000000</u>	3370Lm	26W	4000K	(RA) >80	White (RAL 9003)	15°/30°/45°/60°
<u>1.004A0C830003000000</u>	1250Lm	9.5W	3000K	(RA) >80	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004A0C930003000000</u>	1050Lm	9.5W	3000K	(RA) >90	Grey (RAL 9006)	15°/30°/45°/60°

SKU	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.004A0C940PW3000000</u>	1100Lm	9.5W	4000K	(RA) >90	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004B0C840003000000</u>	1300Lm	9.5W	4000K	(RA) >80	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004C0C930003000000</u>	2000Lm	18.5W	3000K	(RA) >90	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004C0C940PW3000000</u>	2150Lm	18.5W	4000K	(RA) >90	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004D0C830003000000</u>	2400Lm	18.5W	3000K	(RA) >80	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004D0C840003000000</u>	2500Lm	18.5W	4000K	(RA) >80	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004E0C830003000000</u>	3250Lm	26W	3000K	(RA) >80	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004E0C930003000000</u>	3000Lm	30W	3000K	(RA) >90	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004E0C940PW3000000</u>	3200Lm	30W	4000K	(RA) >90	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004F0C840003000000</u>	3370Lm	26W	4000K	(RA) >80	Grey (RAL 9006)	15°/30°/45°/60°
<u>1.004A0B830003000000</u>	1250Lm	9.5W	3000K	(RA) >80	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004A0B930003000000</u>	1050Lm	9.5W	3000K	(RA) >90	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004A0B940PW3000000</u>	1100Lm	9.5W	4000K	(RA) >90	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004B0B840003000000</u>	1300Lm	9.5W	4000K	(RA) >80	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004C0B930003000000</u>	2000Lm	18.5W	3000K	(RA) >90	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004C0B940PW3000000</u>	2150Lm	18.5W	4000K	(RA) >90	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004D0B830003000000</u>	2400Lm	18.5W	3000K	(RA) >80	Black (RAL 9005)	15°/30°/45°/60°

Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.004D0B840003000000</u>	2500Lm	18.5W	4000K	(RA) >80	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004E0B830003000000</u>	3250Lm	26W	3000K	(RA) >80	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004E0B930003000000</u>	3000Lm	30W	3000K	(RA) >90	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004E0B940PW3000000</u>	3200Lm	30W	4000K	(RA) >90	Black (RAL 9005)	15°/30°/45°/60°
<u>1.004F0B840003000000</u>	3370Lm	26W	4000K	(RA) >80	Black (RAL 9005)	15°/30°/45°/60°

© 2019 Light4U BV. All rights reserved. Please visit light4u.io for more information.