



3-Phase LED track spotlight with incorporated driver in Nordic track-adapter available in white, grey and black. Available in CCT from 2700K till 5700K in CRI80 or CRI90, also in special colors for retail use. Reflectors with 15°, 30°, 45° or 60° and various accessories allow a use in a large range of applications. Clear or frosted protective glass on request available.





| Sku                         | Luminous Flux | Connected Load | CCT   | CRI      | Color housing    | Beam angle      |
|-----------------------------|---------------|----------------|-------|----------|------------------|-----------------|
| <u>2.008B0A830003000000</u> | 1750Lm        | 14W            | 3000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008B0A930003000000</u> | 1450Lm        | 14W            | 3000K | (RA) >90 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008B0A940PW3000000</u> | 1550Lm        | 14W            | 4000K | (RA) >90 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008C0A840003000000</u> | 1800Lm        | 14W            | 4000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008C0A930003000000</u> | 2100Lm        | 18.5W          | 3000K | (RA) >90 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008C0A940PW3000000</u> | 2150Lm        | 18.5W          | 4000K | (RA) >90 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008D0A830003000000</u> | 2400Lm        | 18.5W          | 3000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008D0A840003000000</u> | 2500Lm        | 18.5W          | 4000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008E0A830003000000</u> | 3250Lm        | 27W            | 3000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008E0A930003000000</u> | 3000Lm        | 30W            | 3000K | (RA) >90 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008E0A940PW3000000</u> | 3250Lm        | 30W            | 4000K | (RA) >90 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008F0A840003000000</u> | 3350Lm        | 27W            | 4000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |
| <u>2.008G0A830003000000</u> | 4250Lm        | 33W            | 3000K | (RA) >80 | White (RAL 9003) | 15°/30°/45°/60° |

| <b>SKU</b>                  | <b>Luminous Flux</b> | <b>Connected Load</b> | <b>CCT</b> | <b>CRI</b> | <b>Color housing</b> | <b>Beam angle</b> |
|-----------------------------|----------------------|-----------------------|------------|------------|----------------------|-------------------|
| <u>2.008G0A930003000000</u> | 4100Lm               | 38.5W                 | 3000K      | (RA) >90   | White (RAL 9003)     | 15°/30°/45°/60°   |
| <u>2.008H0A840003000000</u> | 4450Lm               | 33W                   | 4000K      | (RA) >80   | White (RAL 9003)     | 15°/30°/45°/60°   |
| <u>2.008H0A940PW3000000</u> | 4400Lm               | 38.5W                 | 4000K      | (RA) >90   | White (RAL 9003)     | 15°/30°/45°/60°   |
| <u>2.008B0C830003000000</u> | 1750Lm               | 14W                   | 3000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008B0C930003000000</u> | 1450Lm               | 14W                   | 3000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008B0C940PW3000000</u> | 1550Lm               | 14W                   | 4000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008C0C840003000000</u> | 1800Lm               | 14W                   | 4000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008C0C930003000000</u> | 2100Lm               | 18.5W                 | 3000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008C0C940PW3000000</u> | 2150Lm               | 18.5W                 | 4000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008D0C830003000000</u> | 2400Lm               | 18.5W                 | 3000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008D0C840003000000</u> | 2500Lm               | 18.5W                 | 4000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008E0C830003000000</u> | 3250Lm               | 27W                   | 3000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008E0C930003000000</u> | 3000Lm               | 30W                   | 3000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008E0C940PW3000000</u> | 3250Lm               | 30W                   | 4000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008F0C840003000000</u> | 3350Lm               | 27W                   | 4000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008G0C830003000000</u> | 4250Lm               | 33W                   | 3000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008G0C930003000000</u> | 4100Lm               | 38.5W                 | 3000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008H0C840003000000</u> | 4450Lm               | 33W                   | 4000K      | (RA) >80   | Grey (RAL 9006)      | 15°/30°/45°/60°   |
| <u>2.008H0C940PW3000000</u> | 4400Lm               | 38.5W                 | 4000K      | (RA) >90   | Grey (RAL 9006)      | 15°/30°/45°/60°   |

| <b>SKU</b>                  | <b>Luminous Flux</b> | <b>Connected Load</b> | <b>CCT</b> | <b>CRI</b> | <b>Color housing</b> | <b>Beam angle</b> |
|-----------------------------|----------------------|-----------------------|------------|------------|----------------------|-------------------|
| <u>2.008B0B830003000000</u> | 1750Lm               | 14W                   | 3000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008B0B930003000000</u> | 1450Lm               | 14W                   | 3000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008B0B940PW3000000</u> | 1550Lm               | 14W                   | 4000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008C0B840003000000</u> | 1800Lm               | 14W                   | 4000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008C0B930003000000</u> | 2100Lm               | 18.5W                 | 3000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008C0B940PW3000000</u> | 2150Lm               | 18.5W                 | 4000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008D0B830003000000</u> | 2400Lm               | 18.5W                 | 3000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008D0B840003000000</u> | 2500Lm               | 18.5W                 | 4000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008E0B830003000000</u> | 3250Lm               | 27W                   | 3000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008E0B930003000000</u> | 3000Lm               | 30W                   | 3000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008E0B940PW3000000</u> | 3250Lm               | 30W                   | 4000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008F0B840003000000</u> | 3350Lm               | 27W                   | 4000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008G0B830003000000</u> | 4250Lm               | 33W                   | 3000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008G0B930003000000</u> | 4100Lm               | 38.5W                 | 3000K      | (RA) >90   | Black (RAL 9005)     | 15°/30°/45°/60°   |
| <u>2.008H0B840003000000</u> | 4450Lm               | 33W                   | 4000K      | (RA) >80   | Black (RAL 9005)     | 15°/30°/45°/60°   |

| <b>Sku</b>                  | <b>Luminous Flux</b> | <b>Connected Load</b> | <b>CCT</b> | <b>CRI</b>  | <b>Color housing</b>   | <b>Beam angle</b> |
|-----------------------------|----------------------|-----------------------|------------|-------------|------------------------|-------------------|
| <u>2.008H0B940PW3000000</u> | 4400Lm               | 38.5W                 | 4000K      | (RA)<br>>90 | Black<br>(RAL<br>9005) | 15°/30°/45°/60°   |

© 2019 Light4U BV. All rights reserved. Please visit [light4u.io](http://light4u.io) for more information.