


Recessed LED downlight supplied in white, grey and black. Available in CCT from 2700K till 5700K in CRI80 or CRI90 and also in special colors for retail use that allows installations in a large range of applications. Also available with IP40 glass from optical side.

PREMIUM WHITE	CRISP WHITE	DIM TO WARM	TUNABLE WHITE	DALI	1-10V	CASAMBI



Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.001A0A940PW5000000</u>	1150Lm	9.5W	4000K	(RA) >90	White (RAL 9003)	50°
<u>1.001B0A830005000000</u>	1300Lm	9.5W	3000K	(RA) >80	White (RAL 9003)	50°
<u>1.001B0A840005000000</u>	1350Lm	9.5W	4000K	(RA) >80	White (RAL 9003)	50°
<u>1.001C0A930005000000</u>	2050Lm	18.5W	3000K	(RA) >90	White (RAL 9003)	50°
<u>1.001C0A940PW5000000</u>	2200Lm	18.5W	4000K	(RA) >90	White (RAL 9003)	50°
<u>1.001D0A830005000000</u>	2500Lm	18.5W	3000K	(RA) >80	White (RAL 9003)	50°
<u>1.001D0A840005000000</u>	2600Lm	18.5W	4000K	(RA) >80	White (RAL 9003)	50°
<u>1.001E0A930005000000</u>	3100Lm	30W	3000K	(RA) >90	White (RAL 9003)	50°
<u>1.001F0A830005000000</u>	3350Lm	26W	3000K	(RA) >80	White (RAL 9003)	50°
<u>1.001F0A840005000000</u>	3500Lm	26W	4000K	(RA) >80	White (RAL 9003)	50°
<u>1.001F0A940PW5000000</u>	3350Lm	30W	4000K	(RA) >90	White (RAL 9003)	50°
<u>1.001G0A930005000000</u>	4250Lm	38.5W	3000K	(RA) >90	White (RAL 9003)	50°
<u>1.001H0A830005000000</u>	4400Lm	33W	3000K	(RA) >80	White (RAL 9003)	50°

SKU	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.001H0A840005000000</u>	4650Lm	33W	4000K	(RA) >80	White (RAL 9003)	50°
<u>1.001H0A940PW50000000</u>	4550Lm	38.5W	4000K	(RA) >90	White (RAL 9003)	50°
<u>1.001A0C930005000000</u>	1100Lm	9.5W	3000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001A0C940PW50000000</u>	1150Lm	9.5W	4000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001B0C830005000000</u>	1300Lm	9.5W	3000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001B0C840005000000</u>	1350Lm	9.5W	4000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001C0C930005000000</u>	2050Lm	18.5W	3000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001C0C940PW50000000</u>	2200Lm	18.5W	4000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001D0C830005000000</u>	2500Lm	18.5W	3000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001D0C840005000000</u>	2600Lm	18.5W	4000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001E0C930005000000</u>	3100Lm	30W	3000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001F0C830005000000</u>	3350Lm	26W	3000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001F0C840005000000</u>	3500Lm	26W	4000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001F0C940PW50000000</u>	3350Lm	30W	4000K	(RA) >90	Grey (RAL 9006)	50°

Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.001G0C930005000000</u>	4250Lm	38.5W	3000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001H0C830005000000</u>	4400Lm	33W	3000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001H0C840005000000</u>	4650Lm	33W	4000K	(RA) >80	Grey (RAL 9006)	50°
<u>1.001H0C940PW5000000</u>	4550Lm	38.5W	4000K	(RA) >90	Grey (RAL 9006)	50°
<u>1.001A0A930005000000</u>	1000Lm, 1100Lm, 1150Lm, 1300Lm, 1350Lm, 2000Lm, 2050Lm, 2200Lm, 2500Lm, 2600Lm, 3000Lm, 3100Lm, 3350Lm, 3500Lm, 4000Lm, 4250Lm, 4400Lm, 4500Lm, 4550Lm, 4650Lm	18.5W, 26W, 30W, 33W, 38.5W, 9.5W	3000K, 4000K	(RA) >80, (RA) >90	Black (RAL 9005), Grey (RAL 9006), White (RAL 9003)	50°
<u>1.001A0B930005000000</u>	1100Lm	9.5W	3000K	(RA) >90	Black (RAL 9005)	50°
<u>1.001A0B940PW5000000</u>	1150Lm	9.5W	4000K	(RA) >90	Black (RAL 9005)	50°
<u>1.001B0B830005000000</u>	1300Lm	9.5W	3000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001B0B840005000000</u>	1350Lm	9.5W	4000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001C0B930005000000</u>	2050Lm	18.5W	3000K	(RA) >90	Black (RAL 9005)	50°

SKU	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.001C0B940PW5000000</u>	2200Lm	18.5W	4000K	(RA) >90	Black (RAL 9005)	50°
<u>1.001D0B830005000000</u>	2500Lm	18.5W	3000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001D0B840005000000</u>	2600Lm	18.5W	4000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001E0B930005000000</u>	3100Lm	30W	3000K	(RA) >90	Black (RAL 9005)	50°
<u>1.001F0B830005000000</u>	3350Lm	26W	3000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001F0B840005000000</u>	3500Lm	26W	4000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001F0B940PW5000000</u>	3350Lm	30W	4000K	(RA) >90	Black (RAL 9005)	50°
<u>1.001G0B930005000000</u>	4250Lm	38.5W	3000K	(RA) >90	Black (RAL 9005)	50°
<u>1.001H0B830005000000</u>	4400Lm	33W	3000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001H0B840005000000</u>	4650Lm	33W	4000K	(RA) >80	Black (RAL 9005)	50°
<u>1.001H0B940PW5000000</u>	4550Lm	38.5W	4000K	(RA) >90	Black (RAL 9005)	50°

© 2020 Light4U BV. All rights reserved. Please visit light4u.io for more information.