



Recessed LED downlight available in white, grey and black. Available in CCT from 2700K till 5700K in CRI80 or CRI90, also in special colors for retail use allow installations in a large range of applications. Also available with IP40 glass from optical side.

PREMIUM WHITE	CRISP WHITE	DIM TO WARM	TUNABLE WHITE	DALI	1-10V	CASAMBI



Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.014A0A930008000000</u>	1100Lm	9.5W	3000K	(RA) >90	White (RAL 9003)	80°
<u>1.014A0A940PW8000000</u>	1200Lm	9.5W	4000K	(RA) >90	White (RAL 9003)	80°
<u>1.014B0A830008000000</u>	1350Lm	9.5W	3000K	(RA) >80	White (RAL 9003)	80°
<u>1.014B0A840008000000</u>	1400Lm	9.5W	4000K	(RA) >80	White (RAL 9003)	80°
<u>1.014C0A930008000000</u>	2100Lm	18.5W	3000K	(RA) >90	White (RAL 9003)	80°
<u>1.014D0A830008000000</u>	2550Lm	18.5W	3000K	(RA) >80	White (RAL 9003)	80°
<u>1.014D0A840008000000</u>	2650Lm	18.5W	4000K	(RA) >80	White (RAL 9003)	80°
<u>1.014D0A940PW8000000</u>	2300Lm	18.5W	4000K	(RA) >90	White (RAL 9003)	80°
<u>1.014E0A930008000000</u>	3150Lm	30W	3000K	(RA) >90	White (RAL 9003)	80°
<u>1.014F0A830008000000</u>	3430Lm	26W	3000K	(RA) >80	White (RAL 9003)	80°
<u>1.014F0A840008000000</u>	3550Lm	26W	4000K	(RA) >80	White (RAL 9003)	80°
<u>1.014F0A940PW8000000</u>	3400Lm	30W	4000K	(RA) >90	White (RAL 9003)	80°
<u>1.014H0A830008000000</u>	4060Lm	33W	3000K	(RA) >80	White (RAL 9003)	80°
<u>1.014H0A840008000000</u>	4700Lm	33W	4000K	(RA) >80	White (RAL 9003)	80°
<u>1.014H0A930008000000</u>	4350Lm	38.5W	3000K	(RA) >90	White (RAL 9003)	80°
<u>1.014H0A940PW8000000</u>	4650Lm	38.5W	4000K	(RA) >90	White (RAL 9003)	80°
<u>1.014A0C930008000000</u>	1100Lm	9.5W	3000K	(RA) >90	Grey (RAL 9006)	80°

SKU	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.014A0C940PW8000000</u>	1200Lm	9.5W	4000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014B0C830008000000</u>	1350Lm	9.5W	3000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014B0C840008000000</u>	1400Lm	9.5W	4000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014C0C930008000000</u>	2100Lm	18.5W	3000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014D0C830008000000</u>	2550Lm	18.5W	3000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014D0C840008000000</u>	2650Lm	18.5W	4000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014D0C940PW8000000</u>	2300Lm	18.5W	4000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014E0C930008000000</u>	3150Lm	30W	3000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014F0C830008000000</u>	3430Lm	26W	3000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014F0C840008000000</u>	3550Lm	26W	4000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014F0C940PW8000000</u>	3400Lm	30W	4000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014H0C830008000000</u>	4400Lm	33W	3000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014H0C840008000000</u>	4700Lm	33W	4000K	(RA) >80	Grey (RAL 9006)	80°
<u>1.014H0C930008000000</u>	4350Lm	38.5W	3000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014H0C940PW8000000</u>	4650Lm	38.5W	4000K	(RA) >90	Grey (RAL 9006)	80°
<u>1.014A0B930008000000</u>	1100Lm	9.5W	3000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014A0B940PW8000000</u>	1200Lm	9.5W	4000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014B0B830008000000</u>	1350Lm	9.5W	3000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014B0B840008000000</u>	1400Lm	9.5W	4000K	(RA) >80	Black (RAL 9005)	80°

Sku	Luminous Flux	Connected Load	CCT	CRI	Color housing	Beam angle
<u>1.014C0B930008000000</u>	2100Lm	18.5W	3000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014D0B830008000000</u>	2550Lm	18.5W	3000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014D0B840008000000</u>	2650Lm	18.5W	4000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014D0B940PW8000000</u>	2300Lm	18.5W	4000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014E0B930008000000</u>	3150Lm	30W	3000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014F0B830008000000</u>	3430Lm	26W	3000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014F0B840008000000</u>	3550Lm	26W	4000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014F0B940PW8000000</u>	3400Lm	30W	4000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014H0B830008000000</u>	4060Lm	33W	3000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014H0B840008000000</u>	4700Lm	33W	4000K	(RA) >80	Black (RAL 9005)	80°
<u>1.014H0B930008000000</u>	4350Lm	38.5W	3000K	(RA) >90	Black (RAL 9005)	80°
<u>1.014H0B940PW8000000</u>	4650Lm	38.5W	4000K	(RA) >90	Black (RAL 9005)	80°

© 2020 Light4U BV. All rights reserved. Please visit light4u.io for more information.